



# R&D STATUS OF HIGH CURRENT ACCELERATORS AT IFP

DENG Jianjun, J.S. Shi, W.P. Xie, L.W. Zhang, K.Z. Zhang, S.P. Feng, J. Li, M. Wang, Y. He, L.S. Xia, Z.Y. Dai, H.T. Li, L. Wen, S.F. Chen, X. Li, Z.P. Huang, Q.G. Lai, M.H. Xia, Y.C. Guan, S.Y. Song, Y.C. Gu, L. Chen, L.J. Zhou, A. He, W.K. Zhou

Institute of Fluid Physics, CAEP  
Presented at EAPPC2010/BEAMS2010  
Oct. 10-14, 2010, Jeju, Korea



# Outline

- ◆ INTRODUCTION
- ◆ R&D OF KEY TECHNOLOGIES AND COMPONENTS FOR HIGH CURRENT ACCELERATORS
- ◆ DEVELOPMENTS OF LINEAR INDUCTION ACCELERATORS
- ◆ R&D OF HIGH CURRENT ACCELERATORS FOR Z-PINCHES
- ◆ R&D OF HIGH CURRENT ACCELERATOR FOR OTHER APPLICATIONS
- ◆ SUMMARY





# INTRODUCTION



- **High current accelerator is of great importance for many applications due to its unique characteristics of high power.**
  
- **Many important applications such as**
  - ◆ **Z-pinches**
  - ◆ **high power microwave**
  - ◆ **free electron laser**
  - ◆ **imploding liner**
  - ◆ **radiography**
  - ◆ **....**





- **Research and development of high current accelerators started at Institute of Fluid Physics in the early of 1960's with development of pulsed accelerator (1.6MV, 5kA, 400ns) for flash X-ray radiography.**



## ■ The researches and developments for high current accelerators at IFP include

key technologies and components

high voltage switches with low jitter

multi-pulse technologies

high speed diagnostics

linear induction accelerators (LIA) with energies ranging from hundreds keV to 20 MeV

Mini-LIA LIAXFU ITS Dragon-I Dragon-II

High current accelerators for Z-pinch and imploding liner

Yang

Primary Test Stand (PTS)


FP-1

X-ray machine and high power microwave




## ■ R&D of High Power Switches With Low Jitter

### ➤ Field-Distortion Spark Gap Switches



**~200 kV**

**Jitter: ~1 ns**



**~300kV**


**Jitter: <1 ns**



## ■ R&D of High Power Switches With Low Jitter

### ➤ Laser-Triggered Spark Gap Switches

Working Voltage: 200 kV~5MV  
Time Jitter: ~ 1 ns



200 kV



5MV switch



## ■ R&D of High Power Switches With Low Jitter

### ➤ Solid State Switches

MOSFET

Photo-conductive  
GaAs SiC

**MoA2-3 Dr. Yuan**

**MoA2-4 Dr. Liu**





## ■ Novel method to generate multi-pulses

High current accelerator with high rep-rate is of great interest in some applications but is extremely difficult to realize due to high power, especially in MHz range.

Several novel methods to generate multi-pulses are proposed and verified

- Double pulses based on Cable-Delay-Method
- Controlled-Pulse-Adder based on spark gap switch



**TuA1-4 Dr. Huang**





## ■ Novel method to generate multi-pulses


### ➤ Double pulses based on Cable-Delay-Method





## ■ Novel method to generate multi-pulses


- Controlled-Pulse-Adder based on spark gap switch





## Linear Induction Accelerator X-ray Facility Upgraded (LIAXFU)

(12MeV, 2.5kA, 60ns, ~4mm, 1995)



Add 4 cavities  
Other improvements

**Linear Induction Accelerator X-ray Facility  
(LIAXF, 10MeV, 2.0kA, 60ns, ~6mm, 1992)**



## **Linear Induction Accelerator X-ray Facility Upgraded (LIAXFU) (12MeV,2.5kA,60ns,~4mm)**

**Injector: Inductive adder -1MV/4cell  
1MeV,3kA,90ns**

**Accelerating section: 32 cells  
350kV,90ns**



## **Integrated Test Stand (ITS) for Intense Beam Physics Researches**

**ITS was built for induction linac technologies and intense beam physics researches in 2004**

**4MeV ,2.5kA, 90ns**





**Injector: Inductive adder -1.0MV/+1.0MV**

**2MeV,2.5kA,90ns**


**8 cells**

**Accelerating section: 8 cells**

**250kV,120ns, 70ns flattop with +/-1% variation**



Studies on multi-pulse intense beam generation, acceleration and transportation have been conducted on ITS






## **Dragon-I Linear Induction Accelerator (19.2MeV,2.54kA,70ns,~1mm, 2003)**

**Injector: Inductive adder -2.1MV/+1.5MV**

**3.6MeV,2.7kA,90ns**

**12 cells**

**Accelerating section: 72 cells**  
**250kV, 120ns,**




**70ns flattop with +/-1% variation**

**WeB3-1 Dr. Liao**

**Beam centroid variation <0.5mm**

**Spot size: ~1mm**

# DEVELOPMENTS OF LIA—Dragon





## ■ Mini-LIA (Double-pulse electron beams)

240keV ,1A , 2x80ns

The **first** LIA

based on the novel Cable-Delay-Method

The **first** designed double pulses LIA  
working at MHz rep-rate in burst mode in the world

The **smallest** LIA in the world



## ■ Mini-LIA (Double-pulse electron beams)


**Designed for multi-pulse beam physics studies**

**Collaborate with Tsinghua Univ.(injector)**

## ■ Mini-LIA (Double-pulse electron beams)



## ■ MiniLIA(Double-pulse electron beams)






## Dragon-II Linear Induction Accelerator

**New accelerator under construction with higher performance**

**Novel design to generate triple pulses based on Controlled-Pulse-Adder**



**Adjustable time interval from hundreds nanoseconds to microseconds**



## Dragon-II Linear Induction Accelerator

**Injector: Inductive adder -1.75MV/+1.25MV**


**3.0MeV,2.5kA,3x90ns, 12 cells, 36 Blumlein PFLs**

**Accelerating section: 80 cells,120 Blumlein PFLs**

**~200kV,120ns, 3x60ns flattop with +/-1% variation**

**Each pulse is controlled by a laser triggered spark gap switch to meet the requirement of time interval between three pulses.**

## Dragon-II Linear Induction Accelerator





## Primary Test Stand(PTS) for Z-Pinch

**PTS is being under construction**

**Stored energy: 7.2MJ**

**Current on load: 8~10 MA**

**Pulse width:130ns**

**Rise time: 90ns**




# HIGH CURRENT ACCELERATORS FOR Z-PINCHES




**PTS**

**24 modules**





## Single module for PTS



**WeA3-3, Dr. Li**



## Primary Test Stand(PTS) for Z-Pinch

**Most part of PTS has been fabricated**


**All the 24 Marx generators have been established and tested**

**Most of the laser triggered switches have been assembled and tested**



## Primary Test Stand(PTS) for Z-Pinch


**Water transmission line and vacuum chamber**





## Primary Test Stand(PTS) for Z-Pinch

**Vacuum chamber**




**Insulator stack**





## Overview of the PDS






## High current accelerator Based on LTD



**1MV, 100kA LTD facility**



**1MA, 100kV LTD module**

**TuA3-4, Dr. Zhou**



## High current accelerator for X-ray machine

**A series of pulsed X-ray machines have been developed with energies ranging from hundreds keV to several MeV**

**Marx-PFL-Diode**

**LTD-Diode**





# SUMMARY



**The R&D status of high current accelerators at IFP are overviewed**

**Activities including R&D of key technologies and components, linear induction accelerators for intense beam physics research and flash X-ray radiography, Z-pinch, accelerators based on LTD technology**

**Two novel methods to generate multi-pulse have been introduced. New accelerators based on such methods are described briefly.**

**Two big high current accelerators(Dragon-II, PTS) are under construction at IFP**





# Thanks...